

## FMS-150, FMM-150, AND FMC-150

**FLUSH MOUNT EMERGENCY PHONES** 

## TYPICAL

Ideal handset in elevator phone cabinet replacement,
Areas of rescue,
Parkades,
Emergency stations,
Hospitals,
Retirement homes,
Building entrances,
Mall security,
Reservation desks,
Automated tellers/
Banking machines

### FEATURES AND BENEFITS



FMS-150







FMC-150

- Call activated by pressing HELP button
- ADA compliant
- Clear audible voice reproduction
- Flashing LED indicates 2-way communication
- Stand-alone operation or integrates with other WebbPhones or LS-250 Rescue Stations
- Ongoing redial of primary and secondary phone numbers until call is established.
- LED indication of call being connected and in-progress
- Capable of receiving external calls
- Self-Diagnostics
- Simple local and remote programmability
- 4 hours battery backup capacity

**Description:** The FMS-150, FMM-150 and FMC-150 are flush mount is a hands-free emergency telephones with exceptional sound quality, operating on a regular analog telephone line. Dust cover back box included.

#### **Ordering Information**

|          |                                  | _  |
|----------|----------------------------------|--|
| FMS-150B | 14 gauge brushed stainless steel | Bilingual silkscreen<br>10"H x 6.5"W x 2"D |
| FMS-150E | 14 gauge brushed stainless steel | English silkscreen<br>10"H x 6.5"W x 2"D   |
| FMM-150B | 14 gauge brushed stainless steel | Bilingual silkscreen<br>13"H x 10"W x 2"D  |
| FMM-150E | 14 gauge brushed stainless steel | English silkscreen<br>13"H x 10"W x 2"D    |
| FMC-150B | 14 gauge brushed stainless steel | Bilingual silkscreen<br>Custom Cut         |
| FMC-150E | 14 gauge brushed stainless steel | English silkscreen<br>Custom Cut           |





# FMS-150, FMM-150, AND FMC-150 FLUSH MOUNT EMERGENCY PHONES

#### **Specification:**

| Power:                        | 120V AC, 60Hz to supplied transformer                                   |
|-------------------------------|---|
| Backup Power:                 | 9V NiCAD rechargeable battery, 4 hour capacity, life expectancy 5 years |
| Phone Line Input:             | Standard analog loop voice grade telephone line                         |
| Microphone:                   | Unidirectional electret condenser, 100Hz - 12kHz                        |
| Speaker:                      | 8 Ohm, 0.25 Watt, 300Hz - 5kHz  |
| Operating Temperature:        | 0 - 60°C  |
| Certification/<br>Compliance: | ADA, FCC - Part 68, Industry Canada, ASME A17.1, CSA<br>B44             |
| Shipping Weight:              | 3.8lb, 1.7Kg  |
| Warranty:                     | 24 months   |

Supplied and serviced by:

information may change without notice

