



# WEBB LOBBY STATION LS-350

Direct replacement for the LS-250 and the LS-100ML

## ANALOG AND IP READY

If your client is unsure of an analog or ip solution, with the ALL NEW LS-350 **your problem is solved!** The LS-350 is **BOTH analog and IP in one device.**

## NETWORK WATCHDOG

With our the Webb Network Watchdog we can switch to Analog lines with no interruption in service if your internet goes down. As an additional option you can add on our cellular backup for a fully redundant solution.

## 10 SIMULTANEOUS LINES, IP OR ANALOG

With 10 simultaneous lines IP or analog it means no more busy signals, when you have an entrapment the faster the person can get help the less likely they will panic.



LS-350-W (without cover)

- Up to 10 emergency phones share 1 to 10 Analog phone lines or IP lines per panel.
- The system is expandable to 200 phones on analog and unlimited IP phones (EX-350 Expansion Stations required)

- “Split Ring” mode is available to first call into the LS-350 followed by a call to a monitoring station if not answered

- Easy to read LCD display (English / French) complies with the CSA B44-19 and ANSI/ASME A17.1-2019 Safety Code for Elevators

- White powder-coat or brushed stainless steel recesses into the wall in the

## LS-350 OPERATION:

### Incoming Calls:

When a call is received, lift the LS-350 handset. The voice prompt will state that there is an “Incoming Webb emergency call. At the tone;

Pressing 1 engages immediate two-way conversation with the caller 2 to hear the location announcement.”

Pressing 2 prompts the playback of the recorded message stating which elevator is calling. Press 1 to engage immediate two-way conversation with the caller.

The LCD indicates which cab is calling as soon as the phone starts ringing. Hang up the handset to end the call.

### Outgoing Calls:

Lift the LS-350 handset. The caller will be prompted to “Enter the cab number you wish to speak to, followed by the \* key.” After several beeps a voice message will state “Connected”, indicating two-way conversation with the passenger in the elevator has been established. Lifting the handset will cut-off any call in progress on the outside line (a Code requirement). Hang up the handset to end the call.

LS-350 has built-in CPC so that call detection is done efficiently with VoIP or Analog lines.



# WEBB LOBBY STATION LS-350

Direct replacement for the LS-250 and the LS-100ML

## EASY INSTALLATION

With the analog or the IP we have preconfigured the basic system and given you a browser based software to speed up your deployments.

## SIP COMPLIANT VoIP

Webb's our LS-350 can be connected to the clients existing VoIP networks internal or externally.

## UNLIMITED PHONE LINES

The LS-350 with the combination of VoIP and Analog Webb has created an unlimited expandability.

## FEATURES AND BENEFITS



- Redundant IP or analog failover
- Software programmable
- Compatible with Webb Safe IP series of products
- Network Watchdog software built in
- SMS or Email Notification
- Call Log
- Group Calling
- 4 Hour Backup
- Main Panel accommodates 10 incoming and 10 Outgoing lines.  
Expandable to 200 incoming analog lines

**Description:** The LS-350 combines design, installation and reliable by exceeding even the recent code changes up to ASME A17.1-2019 and B44-2019. Now the system is virtually plug and play for faster installation. The LS-350 also works with the Webb Phone Lines service which **SAVES UP TO 80%** in monthly phone line charges.

### Specification:

<b>Screen Size:</b>	1"x4"	<b>Expandability:</b>	200 Analog lines in and out Unlimited IP phones
<b>Housing Options:</b>	<ul style="list-style-type: none"> <li>● With or without handset</li> <li>● Custom Mounting plate without back box</li> </ul>	<b>Phone line:</b>	Standard POTS line, VoIP line or Cellular
<b>Expansion wiring:</b>	Via ethernet	<b>Certification:</b>	FCC and CSA
<b>Mounting Options:</b>	Surface or Flush-mount with optional trim ring.	<b>Wiring:</b>	STP 18 to 24 gauge
<b>Finish Options:</b>	Stainless, White or Black	<b>Power:</b>	110VAC, 60Hz
<b>Dimensions:</b>	13.5" (h) x 15" (w) x 3.65 (d)	<b>Weight:</b>	22.5 lbs (10.2) kg

Supplied and serviced by:

*information may change without notice*



Member of the CIS Group of Companies  
Vancouver • Toronto • Montreal • Florida  
1-877-731-1010  
info@webbelectronicinc.com  
[www.webbelectronicinc.com](http://www.webbelectronicinc.com)