



WDP-303 IP DESK PHONE

TYPICAL APPLICATIONS

CACF,
Areas of Rescue,
Emergency Stations,
Hospitals,
Retirement Homes,
Building Entrances,
Mall Security,
Reservation Desks

FEATURES AND BENEFITS



WDP-303-00



HD Voice



HD Video



Android 5.1

- Two-way video communication
- Display all connected cameras in an auto-scrolled 4x2 grid.
- Hands-free speakerphone
- Text communication
- Support 1080P Video
- Volume adjustment
- Clearly audible voice reproduction
- Fully operable by either touchscreen or keyboard
- Mute and Recording features available
- Simple local programmability
- DTMF Relay: support inbound, SIP info, RFC2833
- SIP supports backup SIP servers.
- Integrates seamlessly into the WebbSafe-300 System
- Professional Speaker/handset HD Voice
- Ergonomic handset

Description: The WDP-303 IP desk phone is designed to function with the WebbSafe - 300TM system. With the WDP-303 phones you can seamlessly integrate to the Webb Vision™ system for full video and audio real-time communication.

PHONE OPERATION:

The WDP-303 provides audio and video communication. During the call a two-way video connection with a video enabled elevator can be displayed. Its home screen displays all building/elevator cameras in a 4x2 grid that auto-scrolls every 10 seconds. Touch a single camera view to isolate and enlarge.

Calls are made by either pressing the Hands Free key button or by picking up the handset and then call the desired cab. When a call comes in, it can be answered by either pressing the Hands-Free button or picking up the handset.

Ordering Information

WDP-303-00	Desk Phone	Color: Black
------------	------------	--------------



WDP-303 IP DESK PHONE

RECOMMENDATIONS

Avoid close Proximity to E.M. generating devices.

Specification:

Operating System:	Android 5.1
CPU:	Quad Core
SDRAM:	1GB
Flash:	8GB
Display:	7", 800 x 1200 resolution, ISP multi touch screen
SD Card:	1 SD card slot, supports up to 128GB
Ethernet Port:	1 Ethernet port; 10M/100M/1000M, self-adaptive
Cable Usage:	Cat5
USB:	1 USB 2.0, support U disk, keyboard and mouse
Phone Line Input Protocol:	SIP Protocol over Ethernet, proprietary protocols to achieve compliance
Power:	POE, Max. 30W
Camera:	5 Megapixel
Operating Temperature:	0 - 40°C
Relative Humidity:	10%-65%
Certification/ Compliance:	FCC - Part 68, Industry Canada, ASME A17.1, CSA B44
Distance Between Conductors:	IEEE 802.3 Standard
Size:	200 mm(W) x 150mm(D) x 220 mm(H)
Shipping Weight:	3.5lb, 1.59kg
Warranty:	2 years from date of purchase

Supplied and serviced by:

information may change without notice



Member of the CIS Group of Companies
Vancouver • Toronto • Montreal • Florida
1-877-731-1010
info@webbelectronicsinc.com
www.webbelectronicsinc.com